

January 1971

IS-DOC-12LS  
RM. 1313  
KSC HQS.  
-1-

Brief 71-10001

# NASA TECH BRIEF

## *Kennedy Space Center*



NASA Tech Briefs announce new technology derived from the U.S. space program. They are issued to encourage commercial application. Tech Briefs are available on a subscription basis from the National Technical Information Service, Springfield, Virginia 22151. Requests for individual copies or questions relating to the Tech Brief program may be directed to the Technology Utilization Office, NASA, Code KT, Washington, D.C. 20546.

## Diagnostic Capability Added to Digital Events Evaluator

### The problem:

To improve reliability and decrease trouble shooting time in detecting malfunctions in systems monitored by a digital events evaluator.

### The solution:

The evaluator has been programmed to review the events preceding a system malfunction and print out the most probable cause of the problem automatically.

### How it's done:

The digital events evaluators in use at NASA's Kennedy Space Center employ general purpose digital computers to record for engineering evaluation any changes in the status of certain launch-vehicle and ground-support-equipment components. In the event of malfunction in any of the seven major systems monitored, this record permits system engineers to identify the fault promptly and repair it with minimum down time.

To enhance this diagnostic capability and reduce the chance for human error, the evaluators have now been programmed to analyze in real time the status of the various systems at critical times and to identify any components that are not functioning correctly. The analysis is performed by comparing input data with nominal values stored in sixteen tables. The data comprising these tables can be changed

at will, making it possible to monitor several systems with a single control program.

Enabling of the entire analytic routine and of the system status comparisons is controlled by the system operator. If desired, comparisons can be initiated automatically by a change-of-state in any of the monitored functions and can be delayed from zero to 100 seconds. In addition, each comparison table has an associated system mask which can be used to restrict the comparison to certain preselected critical parameters within a given system.

### Note:

Requests for further information may be directed to:

Technology Utilization Officer  
Kennedy Space Center  
Code AD-PAT  
Kennedy Space Center, Florida 32899  
Reference: B71-10001

### Patent status:

No patent action is contemplated by NASA.

Source: G.E. Hanson and A.S. Frasketi of  
The Boeing Company  
under contract to  
Kennedy Space Center  
(KSC-10526)

Category 09,02